

Red Strikethrough = deleted text

Blue underline = New text

This material is for educational purposes and does not make or imply any assurance or guarantee with respect to the life expectancy, durability or operating performance of materials, appliances, systems and equipment referred to in the information.

Review this document in conjunction with the National Building Code – 2023 Alberta Edition

PART 8 – CODE UPDATE INFORMATION		
NBC(AE) 2019	NBC(AE) 2023	Comments
<p>8.2.1.2. Covered Way Construction</p> <p>1) A covered way shall</p> <p>...</p> <p>f) have a railing 1 070 mm high on the <i>street</i> side where the covered way is supported by posts on the <i>street</i> side,</p> <p>g) be adequately lighted when the <i>public way</i> is lighted, and</p> <p>h) have at each opening for pedestrian access, a gate not less than 1 200 mm high that can be locked or bolted in a closed position.</p>	<p>8.2.1.2. Covered Way Construction</p> <p>1) A covered way shall</p> <p>...</p> <p>f) have a railing 1 070 mm high on the <i>street</i> side where the covered way is supported by posts on the <i>street</i> side, <u>and</u></p> <p>g) be adequately lighted when the <i>public way</i> is lighted, and</p> <p>h) have at each opening for pedestrian access, a gate not less than 1 200 mm high that can be locked or bolted in a closed position.</p>	<p>Clause (h) deleted.</p>
<p>8.2.3.2. Protection from Dangerous Activities</p> <p>1) Operations such as the hoisting of major components onto a tall <i>building</i> or other activities that constitute a hazard from which the public cannot be protected by barricades, covered ways or similar means shall not be carried out until the <i>street</i> or other <i>public way</i> is closed.</p> <p>2) If the safety of pedestrians cannot be assured during hoisting or the undertaking of other hazardous operations, then the gates required by Clause 8.2.1.2.(1)(h) and Sentence 8.2.1.3.(3) that are located in the danger zone shall be closed and locked and pedestrians shall be redirected away from the danger.</p>	<p>8.2.3.2. Protection from Dangerous <u>Overhead</u> Activities</p> <p>1) Operations such as the hoisting of major components onto a tall <i>building</i> or other <u>overhead</u> activities that constitute a hazard <u>to pedestrians below</u> from which the public cannot be protected by barricades, covered ways or similar means shall not be carried out until the <i>street</i> or other <i>public way</i> is closed.</p> <p>2) If the safety of pedestrians cannot be assured during hoisting or the undertaking of other hazardous operations, then the gates required by Clause 8.2.1.2.(1)(h) and Sentence 8.2.1.3.(3) that are located in the danger zone shall be closed and locked and pedestrians shall be redirected away from the danger.</p>	<p>Sentence (2) deleted.</p>